


# CHAPTER 11A FIGURES

## TABLE OF CONTENTS

### **DIVISION VII – FIGURES**

11A-1A	INTERNATIONAL ACCESSIBILITY SYMBOL
11A-1B	OVERHANGING OBSTRUCTION
11A-1C	WIDTH OF ACCESSIBLE ROUTE
11A-1D	WHEELCHAIR TURNING SPACE
11A-1E	MINIMUM CLEAR WIDTH FOR SINGLE WHEELCHAIR
11A-1F	MINIMUM CLEAR WIDTH FOR TWO WHEELCHAIRS
11A-1G	MINIMUM CLEAR FLOOR SPACE FOR WHEELCHAIRS
11A-1H	MINIMUM CLEAR FLOOR SPACE FOR WHEELCHAIRS
11A-1I	FORWARD REACH
11A-1J	SIDE REACH
11A-1K	MINIMUM CLEARANCES FOR SEATING AND TABLE
11A-1L	CORRIDOR OVER 200 FEET
11A-2A	DOUBLE PARKING STALLS
11A-2B	SINGLE PARKING STALLS
11A-2C	DIAGONAL PARKING STALLS
11A-3A	CURB DETAILS
11A-3B	CURB DETAIL
11A-3C	CURB DETAIL
11A-3D	CURB DETAIL
11A-3E	CURB DETAIL
11A-3F	CURB DETAIL
11A-3G	CURB DETAIL
11A-3H	CURB DETAIL
11A-3I	CURB DETAIL
11A-3J	CURB DETAIL
11A-3K	CURB DETAIL
11A-3L	CURB SECTIONS
11A-3M	RETURNED CURB STYLE
11A-3N	TRUNCATED DOMES
11A-3	(RESERVED)
11A-5A	RAMPS AND SIDEWALKS
11A-6A	WARNING STRIPING AND HANDRAIL EXTENSIONS
11A-6B	STAIR HANDRAILS
11A-6C	RAMP DIMENSIONS
11A-6D	RAMP LANDING AND DOORWAY
11A-6E	STAIR HANDRAILS
11A-7A	MINIMUM DIMENSIONS OF ELEVATOR CARS

11A-7B	ELEVATOR CONTROL PANEL
11A-7C	HOISTWAY AND ELEVATOR ENTRANCES
11A-7D	GRAPH OF TIMING EQUATION
11A-8A	FRONT APPROACHES – SWINGING DOORS
11A-8B	HINGE SIDE APPROACHES – SWINGING DOORS
11A-8C	LATCH SIDE APPROACHES – SWINGING DOORS
11A-8D	FRONT APPROACH – SLIDING DOORS AND FOLDING DOORS
11A-8E	SLIDE-SIDE APPROACH – SLIDING DOORS AND FOLDING DOORS
11A-8F	LATCH-SIDE APPROACH – SLIDING DOORS AND FOLDING DOORS
11A-8G	VESTIBULE
11A-8H	VESTIBULE
11A-8I	THRESHOLDS
11A-8J	PLATFORM AT SECONDARY EXTERIOR DOOR
11A-8K	RAMP AT SECONDARY EXTERIOR DOOR
11A-9A	MULTIPLE-ACCOMMODATION TOILET FACILITY
11A-9B	
11A-9C	GRAB BAR SECTION
11A-9D	KNEE CLEARANCE
11A-9E	CLEAR FLOOR SPACE AT BATHTUBS
11A-9F	GRAB BARS AT BATHTUBS
11A-9G	
11A-9H	ROLL-IN SHOWER
11A-9I	ROLL-IN SHOWER
11A-9J	OPEN SHOWER
11A-9K	ALTERNATIVE ROLL-IN
11A-9L	SHOWER WITH WATER CLOSET
11A-9M	WING WALL OR CABINET AT WATER CLOSET
11A-10A	KITCHEN SPECIFICATIONS
11A-11A	WATER FOUNTAINS
11A-11B	MOUNTING HEIGHTS AND CLEARANCES FOR TELEPHONES
11A-11C	INTERNATIONAL TTY SYMBOL
11A-11D	VOLUME CONTROL TELEPHONES
11A-11E	INTERNATIONAL SYMBOL OF ACCESS FOR HEARING LOSS




( a ) SYMBOL PROPORTIONS



( b ) DISPLAY CONDITIONS


THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-1A—INTERNATIONAL ACCESSIBILITY SYMBOL




THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-1B—OVERHANGING OBSTRUCTION



(a) 90° TURN



(c) CHANGE IN LEVEL

(d) CHANGE IN LEVEL

(d) TURNS AROUND AN OBSTRUCTION

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION

FIGURE 11A-1C—WIDTH OF ACCESSIBLE ROUTE




FIGURE 11A-1E—MINIMUM CLEAR WIDTH  
FOR SINGLE WHEELCHAIR






FIGURE 11A-1F—MINIMUM CLEAR WIDTH  
FOR TWO WHEELCHAIRS




(a) 60 INCHES DIAMETER SPACE




(b) T-SHAPED SPACE FOR 180° TURNS

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS  
OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID  
FOR BUILDING DESIGN AND CONSTRUCTION.


FIGURE 11A-1D—WHEELCHAIR TURNING SPACE



PARALLEL APPROACH




CLEAR FLOOR SPACE




FORWARD APPROACH

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION

FIGURE 11A-1G—MINIMUM CLEAR FLOOR SPACE FOR WHEELCHAIRS



(a) CLEAR FLOOR SPACE IN ALCOVES



NOTE : IF  $X > 24$  INCHES, THEN AN ADDITIONAL MANEUVERING CLEARANCE OF 6 INCHES SHALL BE PROVIDED AS SHOWN.


NOTE : IF  $X > 15$  INCHES, THEN AN ADDITIONAL MANEUVERING CLEARANCE OF 12 INCHES SHALL BE PROVIDED AS SHOWN.

(b) ADDITIONAL MANEUVERING CLEARANCE FOR ALCOVES


THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION

FIGURE 11A-1H—MINIMUM CLEAR FLOOR SPACE FOR WHEELCHAIRS





(a) HIGH FORWARD REACH LIMIT




NOTE :  
 X SHALL BE LESS THAN OR EQUAL TO 25 INCHES. Z SHALL BE GREATER THAN OR EQUAL TO X. WHEN X IS LESS THAN 20 INCHES, THEN Y SHALL BE 48 INCHES MAXIMUM. WHEN X IS 20 TO 25 INCHES, THEN Y SHALL BE 44 INCHES MAXIMUM.


(b) MAXIMUM FORWARD REACH OVER AN OBSTRUCTION

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION


FIGURE 11A-11—FORWARD REACH



(a) CLEAR FLOOR SPACE PARALLEL APPROACH




(b) HIGH AND LOW SIDE REACH LIMITS




(c) MAXIMUM SIDE REACH OVER OBSTRUCTION

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION

FIGURE 11A-1J—SIDE REACH




← ACCESSIBLE PATH OF TRAVEL →




THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS, AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.


FIGURE 11A-1K—MINIMUM CLEARANCES FOR SEATING AND TABLE




MINIMUM CORRIDOR WIDTH



MINIMUM WIDTH FOR  
CORRIDORS OVER 200




PASSING ALCOVES FOR CORRIDORS OVER  
200' IN LIEU OF 60" MIN. WIDTH



THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS  
OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID  
FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-1L—CORRIDOR OVER 200 FEET (60 960 mm)



THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS, AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-2A—DOUBLE PARKING STALLS




FIGURE 11A-2B—SINGLE PARKING STALLS







FIGURE 11A-2C—DIAGONAL PARKING STALLS



SECTION A-A

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-3A—CURB DETAILS




SEE FIGURE 11B-19A

THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-3B—CURB DETAIL





SECTION B-B

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-3C—CURB DETAIL




FIGURE 11A-3D—CURB DETAIL




FIGURE 11A-3E—CURB DETAIL

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.




FIGURE 11A-3F—CURB DETAIL

SIDEWALK LESS THAN 60" WIDE




FIGURE 11A-3G—CURB DETAIL

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.




FIGURE 11A-3H—CURB DETAIL




FIGURE 11A-3I—CURB DETAIL

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.






FIGURE 11A-3J—CURB DETAIL




GROOVING DETAIL

FIGURE 11A-3K—CURB DETAIL

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.




SECTION A-A



SECTION B-B

DEPRESS ENTIRE SIDEWALK AS REQUIRED



SECTION C-C


THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-3L—CURB SECTIONS


**FIGURE 11A-3M - RETURNED CURB STYLE (See Figure 11B-21)**

**FIGURE 11A-3N - TRUNCATED DOMES (See Figure 11B-23A)**


**FIGURE 11A-3—(RESERVED)**



(a) SIDEWALK OBSTRUCTIONS



(b) GUIDE RAIL




(c) WHEEL GUIDE


THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-5A—RAMPS AND SIDEWALKS






STAIRS




THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-6A—WARNING STRIPING AND HANDRAIL EXTENSIONS




THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-6B—STAIR HANDRAILS




(a) STRAIGHT RAMP RUN




(b) RAMP WITH TURNING PLATFORM

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS  
OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID  
FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-6C—RAMP DIMENSIONS




( a ) RAMP WITH INTERMEDIATE SWITCH BACK PLATFORM



( b ) RAMP LANDING AT DOORWAY


THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-6D—RAMP LANDING AND DOORWAY




NOTE : INNER HANDRAIL AT LANDINGS OF STAIRS THAT DOUBLE BACK OR IMMEDIATELY TURN SHALL BE CONTINUOUS AND SHALL NOT EXTEND INTO LANDING OR PATH OF TRAVEL.

X : EXTENSION OF HANDRAIL SHALL BE EQUAL TO THE TREAD WIDTH PLUS 12 INCHES.




THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-6E—STAIR HANDRAILS




(a) SIDE OPENING DOOR




(b) CENTER OPENING DOOR

THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION

FIGURE 11A-7A—MINIMUM DIMENSIONS OF ELEVATOR CARS




( a ) ELEVATOR CONTROL PANEL DETAIL



( b ) MAXIMUM INSTALLATION HEIGHTS ABOVE CAB FLOOR


THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-7B—ELEVATOR CONTROL PANEL



NOTE:  
THE AUTOMATIC DOOR REOPENING DEVICE IS ACTIVATED IF AN OBJECT PASSES THROUGH EITHER LINE A OR LINE B. LINE A AND LINE B REPRESENT THE VERTICAL LOCATION OF THE DOOR REOPENING DEVICE NOT REQUIRING CONTACT.

FIGURE 11A-7C—HOISTWAY AND ELEVATOR ENTRANCES



THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-7D—GRAPH OF TIMING EQUATION






FIGURE 11A-8A—FRONT APPROACHES - SWINGING DOORS




FIGURE 11A-8B—HINGE SIDE APPROACHES - SWINGING DOORS

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

#### LEVEL MANEUVERING CLEARANCE AT DOORS




FIGURE 11A-8C—LATCH SIDE APPROACHES - SWINGING DOORS




FIGURE 11A-8D—FRONT APPROACH - SLIDING DOORS AND FOLDING DOORS




FIGURE 11A-8E—SLIDE-SIDE APPROACH - SLIDING DOORS AND FOLDING DOORS






FIGURE 11A-8F—LATCH-SIDE APPROACH - SLIDING DOORS AND FOLDING DOORS

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

LEVEL MANEUVERING CLEARANCE AT DOORS (Continued)



( a ) DOOR IN SERIES




( b ) BOTH DOORS OPEN OUT


(SERVING OTHER THAN A REQUIRED EXIT STAIRWAY)

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-8G—VESTIBULE




(a) DOORS AT ADJACENT WALLS



(b) DOORS AT OPPOSITE WALLS


THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-8H—VESTIBULE  
(SERVING OTHER THAN A REQUIRED EXIT STAIRWAY)



THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

**FIGURE 11A-8I—THRESHOLDS**



**FIGURE 11A-8J – PLATFORM AT SECONDARY EXTERIOR DOOR**








FIGURE 11A-8K – RAMP AT SECONDARY EXTERIOR DOOR




THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-9A—MULTIPLE-ACCOMMODATION TOILET FACILITY






THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION



SECTION THROUGH TYPICAL GRAB BAR


THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION

FIGURE 11A-9C—GRAB BAR SECTION



### SIDE ELEVATION


\*Note: If a minimum 9 inches height of toe clearance is provided, a maximum of 6 inches of the 48 inches of clear floor space required at the fixture may extend into the toe space.



### PLAN VIEW


THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-9D—KNEE CLEARANCE




THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS, AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-9E—CLEAR FLOOR SPACE AT BATHTUBS



( a ) WITH SEAT IN TUB




( b ) WITH SEAT AT HEAD OF TUB

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-9F—GRAB BARS AT BATHTUBS




(a) WATER CLOSET IN ADAPTABLE BATHROOMS



NOTE: THE AREA OUTLINED IN DASHED LINES REPRESENT LOCATIONS FOR FUTURE INSTALLATION OF GRAB BARS FOR TYP. FIXTURE CONFIGURATIONS

(b) LOCATION OF GRAB BAR REINFORCEMENTS FOR ADAPTABLE BATHTUBS



NOTE: THE AREA OUTLINED IN DASHED LINES REPRESENT LOCATION FOR FUTURE INSTALLATION OF GRAB BARS

(a) LOCATION OF GRAB BAR REINFORCEMENTS FOR ADAPTABLE SHOWERS

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-9G






FIGURE 11A-9H—ROLL-IN SHOWER





PERSPECTIVE OF ROLL-IN SHOWER—B  
42" x 48" CALIFORNIA SIZE



ROLL-IN SHOWER—B  
42" x 48" CALIFORNIA SIZE


FIGURE 11A-9I —ROLL-IN SHOWER






THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS  
OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN  
AID FOR BUILDING DESIGN AND CONSTRUCTION

**FIGURE 11A-9J—OPEN SHOWER**



THIS DIAGRAM ILLUSTRATES THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND IS INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.

FIGURE 11A-9K—ALTERNATIVE ROLL-IN



**FIGURE 11A-9L – SHOWER WITH WATER CLOSET**






FIGURE 11A-9M – WING WALL OR CABINET AT WATER CLOSET




TYPICAL KITCHEN



"U" SHAPED KITCHEN


- (1) 30-inch wide counter top space for sink installation with removable base cabinet and finish flooring beneath sink
- (2) 30-inch wide counter top workspace
- (3) 30-inch by 48-inch clear space adjacent to range or cooktop to allow parallel approach
- (4) 30-inch by 48-inch either parallel approach at oven, dishwasher, trash compactor or refrigerator

FIGURE 11A-10A—KITCHEN SPECIFICATIONS




THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION


FIGURE 11A-11A—WATER FOUNTAINS



( a ) SIDE REACH ARRANGEMENT



( b ) FULL HEIGHT ENCLOSURE



( c ) FORWARD REACH ARRANGEMENT

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION

FIGURE 11A-11B—MOUNTING HEIGHTS AND CLEARANCES FOR TELEPHONES



**FIGURE 11A-11C— INTERNATIONAL TTY SYMBOL**



**FIGURE 11A-11D— VOLUME CONTROL TELEPHONES**



**FIGURE 11A-11E— INTERNATIONAL SYMBOL OF ACCESS FOR HEARING LOSS**

THESE DIAGRAMS ILLUSTRATE THE SPECIFIC REQUIREMENTS OF THESE REGULATIONS AND ARE INTENDED ONLY AS AN AID FOR BUILDING DESIGN AND CONSTRUCTION.